

MATERIAL SAFETY DATA SHEET

Section 1 - Product Identification & Use

Product Name: **Advance Balance -**
Synonyms: Advance Balance -250, Advance Balance -2000, Advance Balance -5000
Product Use: For buffering and controlling the pH of Advance-12 Bleach solutions when used for disinfecting & sanitizing applications.
WHMIS Classification: Class E, Corrosive Liquids
TDG Classification: Corrosive liquid n.o.s. (phosphoric acid)
Class 8 (9.2), UN 1760, II
Manufacturer: Advance Chemicals Ltd.
105 - 19613, 56th Avenue
Langley, B.C. Canada V3A 3X7
phone (604) 533-3901, fax (604) 533-5181
Emergency phone: CANUTEC 24 hrs (613) 996-6666

Section 2 - Hazardous Ingredients

Hazardous Components	%(v/v)	C.A.S. No.	LD ₅₀ & LC ₅₀
Phosphoric acid	8-20	7664-38-2	(oral, rat) 1.53 g/kg
Sodium hydroxide	5-20	1310-73-2	(oral, rat) 500mg/kg

Section 3 - Physical Data

Physical state: liquid Boiling point: no data found
Liquid density: 1.08 kg/L Freezing point: 0°C
pH: 1.6 - 2.2 @ 20°C Solubility in water: 100%
Vapour pressure: no data found Evaporation rate: no data
Odour & Appearance: The product is a clear, colourless liquid solution. There may be a slight acid like odour above the open liquid.

Section 4 - Fire or Explosion Hazard

Flammability: The product is not considered to be flammable.
Extinguishing media: Use an extinguishing media for surrounding the fire, or all purpose foam by manufacturer's recommended techniques for large fires. Use water to cool fire exposed containers to prevent vapour build-up and rupture. Water may also be used to flush spills away from dangerous exposures.
Hazardous Combustion Products: This product is considered to be non-flammable, but will decompose when exposed to higher than normal temperatures, producing toxic phosphorous oxide fumes.

Section 5 - Reactivity Data

Stability: Stable under normal ambient conditions. Product will decompose when exposed to very high or extreme temperatures, producing toxic phosphorous oxide fumes.
Incompatible substances: Metals, sulphides, cyanides, fluorides, carbides, silicates and strong oxidizing agents. Do not mix Advance Buffer into, or allow direct contact with sodium hypochlorite solutions (bleach). Dangerous chlorine gas may be produced.
Polymerization: Will not occur.
Conditions to Avoid: Contact with metals produces hydrogen gas, which can form flammable or explosive mixtures in air. Will generate heat when mixed with alkalis. Reaction with sulphides, phosphides, cyanides, acetylides, fluorides, silicides, and carbides, releases flammable and/or poisonous gasses.
DO NOT MIX ADVANCE BALANCE CONCENTRATE INTO, AND NEVER ALLOW DIRECT CONTACT WITH ADVANCE-12 CHLORINE BLEACH (SODIUM HYPOCHLORITE SOLUTIONS). DANGEROUS CHLORINE GAS MAY BE PRODUCED.
Hazardous Combustion Products: This product is considered to be non-flammable, but will decompose when exposed to higher than normal temperatures, producing toxic phosphorous oxide fumes. Wear self contained breathing apparatus.

Section 6 - Toxicological Properties

Acute Toxicity: There is no evidence that phosphorous poisoning can result from contact with phosphoric acid. The chance of pulmonary edema resulting from a mist or spray inhalation is very remote. (from China National Chemicals Import Export Corp., 1991)
Skin contact: Burning, inflammation, blisters.
Eye contact: Burning, watering.

Inhalation: Irritation of mucous membranes, watering of eyes, difficulty breathing, salivation, nausea.

Ingestion: Pain in swallowing, intense thirst, abdominal pain, nausea, concentrated solutions may be fatal

Maximum Exposure Limits for Inhalation of Acid Mist:
8 hours - 1 mg/m³ 15 minutes - 3 mg/m³

Section 7 - Preventative Measures

Personal Protective Equipment: Avoid contact with skin and eyes. Wear chemical protective gloves, goggles and face shield, rubber apron and boots. Eye wash fountains and safety shower facilities should be provided nearby for emergency use.

Respiratory protection: For acidic Buffer mist, use a high efficiency particulate respirator equipped with a full face piece. For concentrations above 50mg/m³, use a continuous supplied air line respirator with a safety hood.

Ventilation Requirements: This product should be used in a well ventilated area at all times. If the solution is to be heated or a mist will be generated during product application, then local exhaust ventilation will be necessary.

Action to take for spills & leaks: Wear chemical protective clothing, rubber gloves and suitable respiratory protection. Small spills should be wiped up with absorbent material and disposed of in government approved waste containers. The spilled product can be neutralized with soda ash (sodium carbonate) or baking soda (sodium bicarbonate) and wet down with a little water to form a slurry. The spill area may then be flushed with large quantities of water. Larger spills should be contained by diking with sand, soil or other absorbent, non-combustible material, then transferred into approved waste containers for proper disposal.

Keep product out of sewers, storm drains, surface run-off water and soil. Restrict access to non-protected personnel. Comply with all government regulations on spill reporting, handling and disposal of waste.

Disposal methods: Dispose of contaminated product and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate federal, provincial and local regulatory agencies to ascertain proper disposal procedures.

Note: Empty containers can have residues, gasses and mists, and are subject to proper waste disposal as mentioned above.

Storage & Handling Precautions: Warning, harmful or fatal if swallowed. Causes eye, skin and respiratory irritation. Avoid contact with eyes and repeated contact with skin and clothing. Do not ingest. Keep away from sources of heat and open flame. Keep container tightly closed when not in use. Store upright in a cool, dry, well ventilated place away from incompatible materials. Do not store product in direct sunlight. Do not use pressure to empty container. Wash thoroughly after handling. Use with adequate ventilation. Tanks must be grounded and ventilated, and ensure proper electrical grounding procedures are in place during product transfer. Pressure may build up in the product container over a period of time, and more frequently in hot weather. Once a week, carefully loosen the bungs or caps to slowly release any pressure.

Repair and Maintenance Precautions: Do not cut, grind, weld or drill in, on or near this container.

Section 8 - First Aid Measures

If inhaled: Remove victim to fresh air. Give artificial respiration if not breathing. Get immediate emergency medical attention. Administer medical oxygen if breathing is difficult.

In case of eye contact: Immediately flush eyes with clean water for at least fifteen (15) minutes, lifting the upper and lower eye lids occasionally. Get immediate emergency medical attention.

In case of skin contact: Immediately flush skin with plenty of clean running water for at least fifteen (15) minutes. Remove contaminated clothing and shoes. If irritation persists after washing, get immediate medical attention. Wash and launder clothes before re-use.

In case of ingestion or swallowing: If victim is conscious and medical attention is not immediately available, dilute stomach contents by giving large amounts of water. Do not induce vomiting.

NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS VICTIM. GET IMMEDIATE EMERGENCY MEDICAL ATTENTION. If vomiting occurs, clear and rinse patient's mouth with water and have the patient drink more water.

Section 9 - Preparation Information

Advance Chemicals Limited expressly disclaims all expressed or implied warranties of merchantability and fitness for a particular purpose with respect to the product provided. The information contained herein is offered only as a guide to the handling of this specific product, and has been prepared in good faith by technically knowledgeable personnel. This M.S.D.S. is not intended to be all inclusive, and the manner and conditions of use may involve other and additional considerations.

Prepared by: Advance Chemicals Ltd. phone (604) 533-3901
6 January, 1997
replaces MSDS of 3 November 1993 & prior
Revised 29 June, 1998, 21 January 2002